

[Baoding Guokun Machinery Co., Ltd](#)

Grooved Tube Fittings




Name	Grooved Tube Fittings
Part Name	<ol style="list-style-type: none">1. 90° Elbow, 45 degree elbow, 22.5 degree Elbow, etc2. Grooved reducer, grooved eccentric reducer, threaded reducer3. Rigid coupling, flexible coupling4. Grooved adapter flange, threaded adaptor flange, split flange5. Grooved end cap, end cap, etc6. Grooved equal cross, grooved reducing cross, threaded reducing cross7. Grooved equal tee, grooved reducing tee, threaded reducing tee, grooved mechanical tee, threaded mechanical tee8. As per your drawings
HS code	730711
Size	1/2"-12"
Material	Ductile Iron, cast iron ASTM A536 Gr. 65-45-12
Pressure	300PSI---2.07Mpa or 230PSI---1.6Mpa
Surface	Painting red, blue, white, orange or Galvanized
Bolts & Nuts	Cold steel Grade 8.8
Application	<ol style="list-style-type: none">1. Fire fighting & fire sprinkler system for commercial and civil fire protection construction, such as water supplying, gas supplying, air-conditioning, etc2. Industrial pipeline system in shipping, mine, oil field, cement, mine piping, chemical plant, etc <p>Ordinary piping delivery in sewage treatment, subway station, airport, seaport, bridge, etc</p> 
Package	Cartons with pallet or wooden case

Web: www.guokuncasting.com

Email: gina@guokuncasting.com

Mobile:+86-18132789710

Baoding Guokun Machinery Co., Ltd

	
Advantage	1. Automatic Vertical Production Line/ DISA Line 2. Painting in our factory 3. Automatic mold with high class tolerance and better finish 4. Testing the leakage or pressure per your orders More than 15 years casting experience and 7 years trading experience

Size Specification

Size	Pipe O.D	Tee		Cross		Reducer		Cap
		Standard	Short	Standard	Short	Grooved	Threaded	
		L	L	L	L	L	L	L
DN/IN	mm/in	mm/in	mm/in	mm/in	mm/in	mm/in	mm/in	mm/in
25 1	33.7 1.327	57 2.244	57 2.244	57 2.244	57 2.244	64 2.52	64 2.52	22 0.866
32 1 1/4	42.4 1.669	70 2.75	60 2.36	70 2.75	60 2.36	64 2.52	64 2.52	22 0.866
40 1 1/2	48.3 1.900	70 2.75	60 2.36	70 2.75	60 2.36	64 2.52	64 2.52	22 0.866
50 2	60.3 2.375	83 3.267	70 2.75	83 3.267	70 2.75	64 2.52	64 2.52	22 0.866
65 2 1/2	73.0 2.875	95 3.74	76 2.99	95 3.74	76 2.99	64 2.52	64 2.52	22 0.866
65 3OD	76.1 3.000	95 3.74	76 2.99	95 3.74	76 2.99	64 2.52	64 2.52	22 0.866
80 3	88.9 3.500	108 4.25	86 3.385	108 4.25	86 3.385	64 2.52	64 2.52	22 0.866
100 4	114.3 4.500	127 5	102 4.016	127 5	102 4.016	76 2.99	76 2.99	25 0.99
125 5.5OD	139.7 5.500	140 5.5	122 4.803	140 5.5	122 4.803	89 3.504	89 3.504	25 0.99
150 6.5OD	165.1 6.500	165 6.5	140 5.511	165 6.5	140 5.511	102 4.016	102 4.016	25 0.99
150 6	168.3 6.625	165 6.5	140 5.511	165 6.5	140 5.511	102 4.016	102 4.016	25 0.99
200 8	219.1 8.625	197 7.75	175 6.89	197 7.75	175 6.89	127 5	127 5	30 1.181

[Baoding Guokun Machinery Co., Ltd](#)

Photos



Web: www.guokuncasting.com

Email: gina@guokuncasting.com

Mobile: +86-18132789710